

SMN. Series Mist Nozzles





Series: SMN

High Pressure Mist Nozzle





Mist Nozzle With Filter **Brass Material** Thread: 10/24", 3/16", M5





Mist Nozzle **Brass Material** Thread: 10/24", 3/16", M5





Mist Nozzle Stainless Steel Material Thread: 10/24", 3/16", M5





Mist Nozzle **Brass Material** Thread: 10/24", 3/16", M5





Mist Nozzle With Cotton Filter Stainless Steel Material Thread: 1/8"



SMN.6112

Mist Nozzle With Cotton Filter Brass Material Thread: 10/24", 3/16", M5





Mist Nozzle With Cotton Filter Brass Material Thread: 1/8"





Roby Mist Nozzle Stainless Steel Material Thread: 1/8"

Nozzle Number	Orifice Ø	Matrix Material	Spray Material	Thread Size	Working Pressure (bar)	Spray Angle	Diameter of Droplet Ø	Spray volume (cc/min)
1	0.1 mm	Brass or Stainless Steel	Ceramic or Stainless Steel	3/16" 10/24" 1/8"	20-80 bar	20-45 degree	3-10 um	10-25
2	0.2 mm							46-89
3	0.3 mm							80-145
4	0.4 mm							95-178
5	0.5 mm							130-243



Series: SMN

Slip lock fittings Connector for high pressure





Slip lock couplin with one nozzle site. specification: 3/8"-3/8"-10/24" 8mm-8mm-10/24" 6mm-6mm-10/24"



SMN.6201B

Slip lock couplin with TWO nozzle site 3/8"-3/8"-10/24" 8mm-8mm-10/24" 6mm-6mm-10/24"



SMN.6119

Slip lock end cap 3/8" 8mm 6mm



SMN.6202

Slip lock elbow 3/8"-3/8" 8mm-8mm 6mm-6mm



SMN.6203

Slip lock Tee 3/8"-3/8"-3/8" 8mm-8mm-8mm 6mm-6mm-6mm



SMN.6204

Slip lock Cross 3/8"-3/8"-3/8"-3/8" 8mm-8mm-8mm-8mm 6mm-6mm-6mm-6mm



SMN.6205

Slip lock couplin 3/8"-3/8" 8mm-8mm 6mm-6mm



SMN.6207

Slip lock transformer 3/8"-1/4" 8mm-1/4" 6mm-1/4"



Series: SMN

Slip lock fittings Connector for high pressure





Slip lock end cap 1/8" female-3/8"



SMN.6221-9

Slip lock couplin with 1/8" Sprey site 1/8" female-3/8"-3/8"





Slip lock Tee 3/8"-6mm-3/8"





SMN.6223

Slip lock elbow 3/8"-6mm

Compression fittings Connector for high pressure



SMN.6210

End cap with one nozzle site Brass material



SMN.6211

Couplin with one nozzle site Brass material 3/8"-3/8"



SMN.6212

Elbow Brass material 3/8"-3/8"



SMN.6213

Tee connector Brass material 3/8"-3/8"-3/8"



Series: SMN

Compression Fittings Connector for high pressure





Cross Brass material 3/8"-3/8"-3/8"-3/8" 8mm-8mm 6mm-6mm



SMN.6215

Couplin without nozzle site Brass material



SMN.6117

Transformer Brass material 3/8"-1/4" male thread 8mm-1/4" 6mm-1/4"



SMN.6221

Couplin with 1/8" thread nozzle site 3/8"-3/8"-1/8" female thread Material: brass with nickle plate



SMN.6220-9

End cap with 1/8" thread nozzle site 3/8"-1/8" female thread



SMN.6222

Couplin with 1/8" thread TWO nozzle site 3/8"-3/8"-1/8"-1/8" female thread Material: Brass with nickle plate



SMN.6227

Shut of valve Brass material



SMN.6228

quick connecting shut of valve 3/8"-3/8"



Series: SMN

Compression Fittings Connector for high pressure





3 Nozzle holder Brass material 3/8"



SMN.6234

4 Nozzle holder Brass material



SMN.6236

6 Nozzle holder Brass material



SMN.6237

3 Nozzle holder 10/24"



SMN.6239

4 Nozzle holder 10/24"





SMN.6238

Description: 5Nozzle site

connectors 10/24"

Material: Brass with nickle plate



SMN.6240

NOZZLE SWIVEL thread size:10/24"





PP-R scissors cutter for high pressure tube





Nozzle extension bar Brass material length:5cm, 10cm, 20cm, 30cm



SMN.6232

2 Nozzle holder Brass material



Series: SMN

Stainless Steel Connector for high pressure





Transformer 304 Stainless Steel material 3/8"-1/4" male thread





End cap with one nozzle site 304 Stainless Steel material 3/8" 8mm-1/4" 6mm-1/4"



SMN.6227B

Shutt of valve Stainless steel material 3/8"-3/8"



SMN.6211B

Coupling with one nozzle site 304 Stainless steel 3/8"-3/8"



SMN.6212B

Elbow 304 stainless steel material 3/8"-3/8"



SMN.6213B

TEE connector 304 stainless steel material 3/8"-3/8"-3/8"



SMN.6214B

Cross 304 stainless steel material 3/8"-3/8"-3/8"-3/8"



SMN.6215B

Coupling without nozzle site 304 stainless steel material 3/8"-3/8"



Series: SMN

Low Pressure Mist Nozzle





Slip lock nozzle Brass material 6mm





Slip lock nozzle 8mm





Slip lock nozzle 8mm & 6mm





Mist Nozzle **Brass Material** Thread: 10/24", 3/16", M5





Mist Nozzle Brass material Auto drain valve Thread: 10/24"-12/24"-M5-1/8"





Slip lock mist nozzle 6mm & 8mm





SMN.6145

Fan mist nozzle 10/24"







End insert

Nozzie Number	Orifice Ø	Matrix Material	Spray Material	Thread Size	Working Pressure (bar)	Spray Angle	Diameter of Droplet Ø	Spray volume (cc/min)
1	0.1 mm	Brass	Ceramic	3/16" 10/24" 1/8"	10-20 bar	20-45 degree	5-20 um	6-25
2	0.2 mm							15-49
3	0.3 mm				5-20 bar			28-80
4	0.4 mm							45-95
5	0.5 mm							60-150



Plastics Connecting Tube Fittings For Low Pressure

Quick Installation, Simple and Flexible, Space-Saving

The Tube Fittings come in a Wide varlety of models to meet all your needs in pneumatic pipping

Even after installation, the direction of tubing can be changed freely

The release ring adopts the ellipse design to make it more convenient and labor saving for disconnection







SPECIFICATION 06-06-10/24" 08-08-10/24" 3/8"-3/8"-10/24"





SPECIFICATION 6-6mm 8-8mm 10-10mm 12-12mm





SPECIFICATION 08-06mm 10-08mm 12-08mm 12-06mm





SMN.103

SPECIFICATION 06-06mm 08-08mm 10-10mm 12-12mm



SMN.104

SPECIFICATION 06-06-06mm 08-08-08mm 10-10-10mm 12-12-12mm





SMN.105

SPECIFICATION 06-06mm 08-08mm 10-10mm 12-12mm



Plastics Connecting Tube Fittings For Low Pressure

Quick Installation, Simple and Flexible, Space-Saving

The Tube Fittings come in a Wide varlety of models to meet all your needs in pneumatic pipping

Even after installation, the direction of tubing can be changed freely

The release ring adopts the ellipse design to make it more convenient and labor saving for disconnection





SPECIFICATION 06-06-06mm 08-08-08mm 10-10-10mm 12-12-12mm



SMN.108

SPECIFICATION 8-8mm 10-10mm 12-12mm



SMN.109

SPECIFICATION 08-06mm 10-08mm 12-10mm



SMN.110

SPECIFICATION 06-06mm 08-08mm 10-10mm 12-12mm



SMN.139

SPECIFICATION 06-06mm 08-08mm 10-10mm 12-12mm



SMN.140

SPECIFICATION 06-06mm 08-08mm 10-10mm



SMN.116

SPECIFICATION 06-06-06-06mm 08-08-08-08mm 10-10-10-10mm 12-12-12mm



SMN.128

SPECIFICATION 06-10mm 06-12mm 08-10mm 08-12mm 10-12mm



Plastics Connecting Tube Fittings For Low Pressure

Quick Installation, Simple and Flexible, Space-Saving

The Tube Fittings come in a Wide varlety of models to meet all your needs in pneumatic pipping

Even after installation, the direction of tubing can be changed freely

The release ring adopts the ellipse design to make it more convenient and labor saving for disconnection





SMN.130

SPECIFICATION 06mm 08mm 10mm 12mm





SPECIFICA	NOITA
06mm-1/8"	Male
06mm-1/4"	Male
06mm-3/8"	Male
06mm-1/2"	Male

 SPECIFICATION
 SPECIFICATION
 S

 08mm-1/8" Male
 10mm-1/8" Male
 1

 08mm-1/4" Male
 10mm-1/4" Male
 1

 08mm-3/8" Male
 10mm-3/8" Male
 1

 08mm-1/2" Male
 10mm-1/2" Male
 1

| ICATION | SPECIFICATION | /8" Male | 12mm-1/8" Male | 12mm-1/4" Male | 12mm-3/8" Male | 12mm-1/2" Male | 12mm-1/2" Male |





SPECIFICATION 06mm-1/8" Female 06mm-1/4" Female 06mm-3/8" Female 06mm-1/2" Female SPECIFICATION 08mm-1/8" Female 08mm-1/4" Female 08mm-3/8" Female 08mm-1/2" Female SPECIFICATION 10mm-1/8" Female 10mm-1/4" Female 10mm-3/8" Female 10mm-1/2" Female SPECIFICATION 12mm-1/8" Female 12mm-1/4" Female 12mm-3/8" Female 12mm-1/2" Female



SMN.136

SPECIFIC/	NOITA
06mm-1/8"	Male
06mm-1/4"	Male
06mm-3/8"	Male
06mm-1/2"	Male

SPECIFICATION 08mm-1/8" Male 08mm-1/4" Male 08mm-3/8" Male 08mm-1/2" Male SPECIFICATION 10mm-1/8" Male 10mm-1/4" Male 10mm-3/8" Male 10mm-1/2" Male SPECIFICATION 12mm-1/8" Male 12mm-1/4" Male 12mm-3/8" Male 12mm-1/2" Male



SMN.135

SPECIFICATION 06mm06mm-1/8" Female 06mm-06mm-1/4" Female 06mm-06mm-3/8" Female 06mm-06mm-1/2" Female SPECIFICATION 08mm-08mm-1/8" Female 08mm-08mm-1/4" Female 08mm-08mm-3/8" Female 08mm-08mm-1/2" Female SPECIFICATION 10mm-10mm-1/8" Female 10mm-10mm-1/4" Female 10mm-10mm-3/8" Female 10mm-10mm-1/2" Female SPECIFICATION 12mm-12mm-1/8" Female 12mm-12mm-1/4" Female 12mm-12mm-3/8" Female 12mm-12mm-1/2" Female



Plastics Connecting Tube Fittings For Low Pressure

Quick Installation, Simple and Flexible, Space-Saving

The Tube Fittings come in a Wide varlety of models to meet all your needs in pneumatic pipping

Even after installation, the direction of tubing can be changed freely

The release ring adopts the ellipse design to make it more convenient and labor saving for disconnection





SPECIFICATION 08mm-10/24"



SMN.111

SPECIFICATION 6-6mm 8-8mm 10-10mm 12-12mm



SMN.154

SPECIFICATION 06-06-06mm 08-08-08mm 10-10-10mm 12-12-12mm 08-06-08mm 10-08-10mm



SMN.153

SPECIFICATION 06-06-06mm 08-08-08mm 10-10-10mm 12-12-12mm 08-08-06mm 10-10-08mm



SMN.137

SPECIFICATION 06mm 08mm 10mm 12mm



SMN.334

SPECIFICATION 06-06mm 08-08mm 10-10mm 12-12mm



SMN.1402

Coupling with 10/24" thread Specification: 1/4"



SMN.128

Hose Adaptor Specification: 3/4" female thread 1/4" quick connected



Plastics Connecting Tube Fittings For Low Pressure

Quick Installation, Simple and Flexible, Space-Saving

The Tube Fittings come in a Wide varlety of models to meet all your needs in pneumatic pipping

Even after installation, the direction of tubing can be changed freely

The release ring adopts the ellipse design to make it more convenient and labor saving for disconnection





BULKHEAD

Specification:1/4"




















Series: SMN

High Pressure Fire Nozzle





•Drops: Fine in size and evenly distributed.


-Material : BRASS/SS

-Features : Fixed, porous jet, covering a wide

Low water consumption, large surface area, can dissolve, adsorption part of the smoke and gas,

clean the fire environment





·Dust control ·Fire extinguishing ·Smoke washing and

Nozzle Type	Flow Coefficient (K)	Working Pressure (Mpa)	Working Flow (L/min)
SMT-0.3/10	0.3	10.0-14.0	3.0-3.5
SMT-0.5/10	0.5	10.0-14.0	5.0-5.9
SMT-0.7/10	0.7	10.0-14.0	7.0-8.3
SMT-0.9/10	0.9	10.0-14.0	9.0-10.6
SMT-1.0/10	1.0	10.0-14.0	10.0-11.8
SMT-1.2/10	1.2	10.0-14.0	12.0-14.2
SMT-1.5/10	1.5	10.0-14.0	15.0-17.7
SMT-1.7/10	1.7	10.0-14.0	17.0-20.01
SMT-2.0/10	2.0	10.0-14.0	20.0-23.7
SMT-2.5/10	2.5	5.0-10.0	12.5-29.6
SMT-3.0/10	3.0	5.0-10.0	15.0-35.5
SMT-3.5/10	3.5	5.0-10.0	17.5-41.4
SMT-4.0/10	4.0	3.5-10.0	14.0-47.3
SMT-4.5/10	4.5	3.5-10.0	15.8-53.2
SMT-5.0/10	5.0	3.5-10.0	17.5-59.2
SMT-5.5/10	5.5	3.5-10.0	19.3-65.1